

TO CLEAR A SPOOL FILE.

CAUTION: When you delete a spool file, it is gone. You cannot retrieve it once you hit enter. Double verify what you are deleting.

On a command line type: DLTSPLF<F4>

Specifies which group of files should be selected for deletion. Files can be selected based on user, device, form type, and user data. Only files that meet each of the values are selected.

The possible values for the user are:

- *CURRENT
 - Only files created by the user running this command are selected.
- *ALL
 - Files created by all users are selected.
- user-name
 - Specify a user name. Only files created by that user name are selected.

The possible values for the device are:

- *ALL
 - Files on any device-created or user-created output queue are selected.
- *OUTQ
 - All files on any user-created output queue are selected. A user-created output queue is any output queue that is not automatically created by a device. A user-created output queue does not generally have the same name as a device, but if it does, it does not reside in library QUSRSYS.
- device-name
 - Specify a device name. Only files on the device created output queue for that device are selected. A device created output queue is one that has the same name as a device and resides in the QUSRSYS library. Unless it already exists, it will automatically be created by the system when the device is created. A device created output queue cannot be deleted.

The possible values for the form type are:

- *ALL
 - Files for all form types are selected.
- *STD
 - Only files that specify the standard form type are selected.
- form-type
 - Specify the form type to select the file.

The possible values for the user data are:

- *ALL
 - Files with any user data tag specified are selected.
- user-data
 - Specify the user data tag to select the file.